



Bearing No.	Boundary dimensions(mm)						Basic load ratings(kN)		Mass(kg)
	d	D	B	T	r min	r1 min	dyc(Cr)	stc(Cor)	
77928	139.7	200.025	157.162	160.338	1.1	1.8	535	1870	16.2
2077930	150	210	165	165	0.7	2.3	600	1590	21.2
77730	150	225	136	136	3	2.5	540	1460	17.7
2077134	170	260	230	230	3	2.5	940	3100	43
77736	180	280	180	180	3	2.5	835	2540	39.6
77740	200	310	200	200	3	2.5	1970	1520	55.6
20777140	200	310	275	275	3	2.5	1230	4200	75.1
77741	205	320	205	205	4	3	1060	2850	55.4
20777144	220	340	305	305	4	3	2290	5950	99.5
20777148	240	360	310	310	4	3	3300	210	90.5
77750K	250	460	270	270	5	4	2250	6400	192
382952/HC	260	360	265	265	3	2.5	1730	5050	77.8
77752	260	400	255	255	3.7	7.5	1480	4950	117

7752G	260	400	255	255	5	4	1910	490	117
382052	260	400	345	345	5	4	2850	7700	161
777752	260	440	300	300	2	5	2670	5850	182
77756	280	420	250	250	5	5	1540	5300	119
77860U	300	420	310	310	4	3	2020	8100	134
2077160	300	460	390	390	5	4	3850	10200	222
77760U	300	500	350	350	5	4	2730	8900	280
2077164	320	480	380	380	5	4	3000	11500	252
2077968	340	460	310	310	4	4	2200	9300	147
371068	340	520	325	325	5	4	3200	8200	247
77872	360	480	375	375	4	4	2550	11800	197
1077772	360	600	420	420	4.7	4.7	3950	13500	388
77776	380	550	330	350	5	5	2490	9450	273
3077776	380	620	388	388	6	6	3450	11600	443
381176/HC	380	620	420	420	5	4	5050	12600	485
381176/HCC9	380	620	420	420	5	4	5050	12600	485
77779	395	545	268.7	288.7	4	7.5	2130	6500	194
77779K	395	545	268.7	288.7	4	7.5	2130	6500	194
77779U	395	545	268.7	288.7	4	7.5	2130	6500	194
77880	400	540	280	280	3.7	7.5	2450	6500	187
380680/HC	400	540	400	400	5	5	6350	13300	262
381080/HC	400	600	356	356	5	4	3400	12400	345
380684/HC	420	560	437	437	5	5	7180	16300	298
1077784	420	700	480	480	6	5	5100	18200	749
381184	420	700	480	480	6	5	9550	11900	755
77888U	440	620	454	454	6	6	6050	1880	432
77888	440	620	454	454	6	6	6050	18800	432
77888	440	650	355	355	6	5	3350	12100	385
77888K	440	650	355	355	6	6	3350	12100	385
381088X2/HG	440	650	355	355	6	5	4550	12300	402
381992/HC	460	620	310	310	5	4	5600	3450	260
381992/HCC9	460	620	310	310	5	4	5600	3450	260
77982U	460	650	474	4746	6	6	4500	20000	506

381192X3/HC	460	730	440	440	4	7.5	5600	14800	663
381192X3/HCC9	460	30	440	440	4	7.5	5600	14800	663
381096	480	700	420	420	5	5	4300	16900	582
77196	480	700	420	420	6	5	5350	15500	535
380698/HC	490	625	385	385	7	4	4900	16500	278
3810/530	530	780	450	450	6	5	6550	18200	745
779/540	540	690	400	400	2	5	5700	11400	375
3819/560/HC	560	750	368	368	5	4	7850	15800	447
3811/560	560	920	620	620	7.5	6	18200	32000	1690
779/600	600	800	365	365	5	5	4000	18100	489
10779/600	600	800	380	380	5	4	4000	18100	497
3810/600/HC	600	870	480	480	6	6	6150	25500	992
10777/600	600	980	650	650	7.5	7.5	9650	37500	1970
3819/630/HC	630	850	418	418	6	6	5000	22100	682
771/630	630	920	515	515	7.5	7.5	6550	27500	1190
3811/630/HC	630	1030	670	670	7.5	6	15000	42000	2200
777/650C	640	1030	560	560	7.5	12	16000	39300	1770
777/650K	650	1030	560	560	7.5	12	16000	39300	1735
777/650	650	1030	560	560	7.5	12	16000	39300	1720
777/650U	650	1030	560	560	7.5	12	16000	39300	1723
777/650UY	650	1030	560	560	7.5	12	16000	39300	1712
3806/660X4/HC	660.01	855.015	319.99	319.99	12	5.2	4750	17000	495
10779/670	670	900	412	412	6	6	5250	2460	773
779/710	710	900	410	410	3	6	5350	27500	650
10777/750	750	1220	840	840	9.5	9.5	16100	68500	3985
3806/780/HCC9	780	1220	840	840	6	6	21100	70500	3810